

NATIONAL FLEX PUTTY

DESCRIPTION	It is a special glazing putty based on Nitrocellulose / Alkyd for use on wooden & steel surfaces.
RECOMMENDED USE	As a body filler for automobiles and for leveling wooden surfaces.

TECHNICAL DATA

Colors	Red, Red Brown, Grey, White, Black.
Gloss (60°)	Matt.
Solid by Weight% (110°C)	55 ± 1 %
Viscosity (20°C)	Thick Viscosity.
Specific Gravity	1.28 ± 0.02
Covering Capacity	3 - 4 m ² /Lit. (D.F.T. 30 μ).
Film Thickness	Single pack, ready to use.

DRYING TIME

Touch dry	30 min.
Sanding Time	After 2 hrs.
Hard dry	3 – 4 hrs.

SURFACE PREPARATION

To be applied over **National N.C Primer** and the primered surface should be dry, clean and free from any loose particles.

APPLICATION DATA

Application Methods	Glazing Knife.
Thinning / Cleaning of Tools	Thinner 121 or National Thinner.
Guiding Data for Airless Spray	Recommended 20 - 30 microns per coat (or as necessary depends upon surface).

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months, in original sealed container, with proper storage conditions.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE NO. & DATE	(3) - June 2017

NOTE:

We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.