



National Antique Decoration

DESCRIPTION	It is a specially formulated water based finish designed to give the surface decor effects which stimulate prestigious architecture of the ancient places.
RECOMMENDED USE	On Concrete, Gypsum Boards, Plaster and Woodwork.

TECHNICAL INFORMATION

Covering Capacity	3 - 4 m ² / 1/4 Lit. (depending on the desired effect.)
Viscosity	After mixing = 35 POISE
Density	After mixing = 1
Drying Time	Touch dry : 30 min. Hard dry : 60 min.

SURFACE PREPARATION

Surface must be dry, free from oil, dust, efflorescence etc.

APPLICATION DATA

Application Methods	Special Brush and Trowel.
Thinning / Cleaning of Tools	Water.

CONDITIONS DURING APPLICATION

Application Method:

Apply two coats of antique base on the wall by Using a paint roller.

Mix colored antique base with antique filler.

Use a special brush to paint the product randomly.

After 5-10 minutes later, and before the substance is dry, use a paint trowel to crush the grains.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(1) - Jan. 2019

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.