



NATIONAL FIBRE
DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL FIBRE

PRODUCT DESCRIPTION	National fibre wall covering are mainly used for interior decoration application. These fibres are based on fibre glass filaments. Useful for getting different pattern, can be painted using various systems.
----------------------------	--

RECOMMENDED USES	<ul style="list-style-type: none"> - Suitable for painting for all interior surfaces. - Renovation of old buildings, houses. - For decoration of restaurants, hotels, banks etc.
-------------------------	---

TECHNICAL DATA

NATIONAL FIBRE (FIBRE GLASS FABRIC)	WEIGHT (g /sq. m)	SIZE
N – 103	110	In roll of 50 meter by one meter
N – 022	165	In roll of 50 meter by one meter
N – 058	180	In roll of 50 meter by one meter
N – 060	180	In roll of 50 meter by one meter
N – 064	180	In roll of 50 meter by one meter
N – 073	180	In roll of 50 meter by one meter
N – 090	180	In roll of 50 meter by one meter
N – 095	180	In roll of 50 meter by one meter

APPLICATION DATA

APPLICATION PROCEDURE	<ul style="list-style-type: none"> - Apply National Primer Sealer. Allow it to dry. - Apply National White Glue. - Fix National Fibre while the glue is still wet. - Apply first coat of National Matt Emulsion (OR) National Acrylic Rock Topcoat. - Apply second coat of National Matt Emulsion (OR) National Acrylic Rock Topcoat. - For more details please refer to National Fibre Brochure.
------------------------------	---

MISCELLANEOUS DATA

DRYING TIME @ 30°C – 22 HOURS	Application of National White Glue, then fixing of National Fibre, Application of Topcoat.
--------------------------------------	--

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

This data sheet supersedes all previous issued.
Issued: 0718