



NATIONAL MODERN

DESCRIPTION	A Styrene Acrylic base economical matt finish with good hiding power, excellent washability and alkali resistance.
RECOMMENDED USE	As an Interior and Exterior paint.

TECHNICAL INFORMATION

Colors	As per shade card.
Finish	Matt
Specific Gravity	1.49 ± 0.02
Solid by Weight %	64.3 ± 2%
VOC (Volatile Organic Compounds)	<40 gm/L
Covering Rate (2 coats 20% dilution)	6 - 7 m ² /Lit.

SURFACE PREPARATION

If the surface needs to be prepared before painting **National Bond Sealer** and **National Antique Stucco** (Interior only) are suitable.

APPLICATION DATA

Application Methods	Brush, Roller, Airless or Conventional Spray.
Thinning / Cleaning of Tools	Water
Guiding Data for Airless Spray	Nozzle Tip: 0.021" - 0.027" Nozzle Pressure: 2100 P.S.I. Spray Angle: 65° - 80°

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(2) - June 2017

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.