



NATIONAL JOINTS PUTTY

DESCRIPTION	A specially formulated water base putty designed to fill the cracks of surfaces, paintable, and has elastic properties and retains its adhesion.
RECOMMENDED USE	Used for cracks, joints, and holes on all common building surfaces including Timber, Exterior and Interior.

TECHNICAL INFORMATION

Colors	White.
Specific Gravity	1.60 - 1.65
Solid by Weight %	75 - 80 %
Hiding Power	5 - 6 m ² /Lit.
Drying Time	Touch dry : 2 hrs. Recoatable: 6 hrs. Hard dry: 24 hrs.

SURFACE PREPARATION

Surface must be dry, free of oil, dust, efflorescence etc...

APPLICATION DATA

Application Methods	Trowel, Scraper, Knife, Blade.
Thinning	Ready to use as such.
Cleaning of Tools	Water

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the air temperature and relative humidity measured in the substrate vicinity.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	24 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(2) - June 2017

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.