



National Expressions Special Effect

DESCRIPTION	A Vinyl Acetate / Vinyl Versatate Copolymer base creative finish which makes it easy to create beautiful, unique and versatile paint effects such as rag rolling, color washing, sponging, dragging etc...
RECOMMENDED USE	Interior and Exterior. On Concrete, Gypsum Boards, Plaster and Woodwork.

TECHNICAL INFORMATION

Colors	As per shade card.
Viscosity 25°C	11 - 13 Poise.
Specific Gravity	1.2 ± 0.05
Solid by Weight %	40 ± 2%
Covering Capacity	15 - 20 m ² /Lit. may be more, (depending on the desired effects).
Drying Time	Touch dry : 2 hrs. Recoatible: 6 hrs. Hard Dry: 24 hrs.

SURFACE PREPARATION

Surface must be dry, free from oil, dust, efflorescence etc...

APPLICATION DATA

Application Methods	Brush, Roller and Special tools.
Thinning / Cleaning of Tools	Water.

CONDITIONS DURING APPLICATION

Application method:

Apply the first coat of **National Bond Sealer** to ensure maximum adhesion to surface. Then apply **National Vinyl Silk Emulsion** to the surface and allow dry for (6 - 8 hrs). Second coat apply **National Expressions Special Effect** using one of the following methods depending on the desired effect:

- **Sponging Effect:** Pour paint into a roller tray and lightly dampen sponge before use. Lightly load the sponge evenly with paint and apply using a gentle dabbing motion.
- **Stippling:** Apply paint directly onto the wall using a stippling tool or using a brush or roller and then “stipple off” using a sharp bouncing action.
- **Rag Rolling:** Apply paint evenly over the surface with brush or roller. Gather a lint free rag into a loose bunch and lightly roll or dab the surface. Rags should be continuously shaken out and rinsed to avoid clogging.
- **Dragging:** Apply paint by roller then lightly drag brush in even downward strokes.
- **Color Washing:** Apply paint using a color wash brush or damp sponge in light random strokes over previously painted surfaces.



MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	<ul style="list-style-type: none">- Ensure good ventilation during application and drying.- Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.- Keep out of reach of children.
TDS ISSUE No. & DATE	(2) - June 2017

NOTE: *We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.*