



NATIONAL EXPRESSIONS STUCCO

DESCRIPTION	A Styrene-Acrylic base finish which has high adhesion to substrates and is an ideal filler for giving style decoration.
RECOMMENDED USE	For Interior only. Concrete, Gypsum Boards, Plaster and Woodwork.

TECHNICAL INFORMATION

Color	As per shade card.
Viscosity (25°C)	Thick paste.
Specific Gravity	1.52
Solid by Weight %	60 ± 2%
Covering Capacity	3-4 m ² /Lit. (depending on the thickness and the desired effect).
Drying Time	Touch dry : 2 hrs. Recoatable: 6 hrs.

SURFACE PREPARATION

Surface must be dry, free from oil, dust, efflorescence etc...

APPLICATION DATA

Application Methods	Putty Knife.
Thinning / Cleaning of Tools	Water.

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity

Application method:

Apply a first coat of **National Bond Sealer** to ensure maximum adhesion to the surface. Then apply a coat of **National Trust or National Top**, after drying apply National Expressions Stucco over the surface and allow the product to dry for 6 - 8 hrs. Apply a second coat as per the first coat and after the finish has dried, polish by smoothing over the surface. To guarantee water-repellency and washability apply a clear topcoat based on pure acrylic binder after 4 - 5 days.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	18 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE NO. & DATE	(2) - June 2017

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.