

NATIONAL FIRE RETARDANT THINNER

DESCRIPTION	A special Thinner for Fire Retardant Coating.
RECOMMENDED USE	As a reducer Thinner for Fire Retardant Coating.

TECHNICAL INFORMATION

Appearance	Transparent Liquid.
Specific Gravity @ 15 °C	0.77 - 0.79
Viscosity by FordCup B4	12 - 14 Seconds.
Odour	Mild
Flash Point	41°C
Refractive Index @ 20°C ASTM D-1218	1.432
Distillation Range @ 101,3 kpa (ASTM D-1078)	150 - 197°C

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	24 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(1) - Jan 2014

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.