

NATIONAL COLD BITUMEN

DESCRIPTION	Cold liquid Bitumen with added special materials, acts as a water
	insulator and vapor barrier for concrete and masonry by closing pores. Has good adhesion, good flexibility, and high resistance to rot.
RECOMMENDED USE	On Concrete, Brickwork, Masonry, etc

TECHNICAL INFORMATION

Colors	Black
Finish	Matt
Viscosity	10 Poise.
Specific Gravity	1.2 g/ml
Solid by Volume %	85 ± 2
Flash Point	> 35 °C
Covering Rate	1-2 m²/Lit without thinning, depends on the thickness of application.
Drying Time	Touch dry: 3 hrs, Hard dry: 12 hrs.
-	Drying time might be affected by temperature and humidity.

SURFACE PREPARATION

Surface should be dry, clean and free from dirt, dust or grease.

APPLICATION DATA

Application Methods	Brush, Roller.
Thinning / Cleaning of Tools	White spirit

CONDITIONS DURING APPLICATION

Temperature of the substrate should be minimum 5°C

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	12 months.
SAFETY / HEALTH	 Ensure good ventilation during application and drying. Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. Keep out of reach of children.
TDS Issue No. & date	Issue (2), June 2022

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.