

NATIONAL N.C. WOOD STAIN

DESCRIPTION	A decorative color stain based on Nitrocellulose Resin which gives a transparent wood color, weather resistant and durable.
RECOMMENDED USE	On wooden surfaces.

TECHNICAL DATA

Colors	As per shade card.
Viscosity (25°C)	30 - 35 sec.
Specific Gravity	0.93 ± 0.02
Solid by Weight %	18 ± 3 %
Covering Capacity	15 m ² /Lit.
Flash Point	8°C

DRYING TIME

Touch dry	10 - 15 min.
Recoatable	30 - 45 min.

SURFACE PREPARATION

Surface should be dry, clean and free from dust.

APPLICATION DATA

Application Methods	Brush or spray.
Thinner / Cleaning of Tools	National Thinner 121 or National Special Thinner .

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	24 months, in original sealed container, with proper storage conditions.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE NO. & DATE	(2) - April 2014
NOTE:	<i>We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.</i>