



NATIONAL EMULSION SN PLUS

DESCRIPTION	A Styrene Acrylic base economical matt finish with good hiding power, and alkali resistance.
RECOMMENDED USE	As an Interior , On Concrete, Gypsum Boards, Plaster .

TECHNICAL INFORMATION

Color	As per shade card.
Viscosity (25°C)	26-30 POISE
Specific Gravity	1.61 \pm 0.02
Solid by Weight %	62 % \pm 2
Covering Rate (2 coats 25% dilution)	6 - 7 m ² /Lit.
VOC (Volatile Organic Compounds)	10-20 gm/L
Drying Time	Touch dry : 30 min Recoatable: 2 hrs

SURFACE PREPARATION

If the surface needs to be prepared before painting, Bond Sealer and Wall Putty are suitable.

APPLICATION DATA

Application Methods	Brush, Roller, Airless or Conventional spray.
Thinning / Cleaning of Tools	Water.
Guiding Data for Airless Spray	Nozzle Tip: 0.021" - 0.027" Nozzle Pressure 2100 P.S.I. Spray Angle: 65° - 80°

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	- Refer MSDS
TDS ISSUE No. & DATE	N/A

NOTE: *We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.*