



NATIONAL BOND TOP ALKALI RESISTANT

DESCRIPTION	Special primer based on acrylic polymer having good adhesion, penetrating into cementitious substrates, highly resistant for weathering recommended as primer for exterior paints.
RECOMMENDED USE	Exterior concrete, plaster.

TECHNICAL INFORMATION

Colors	Semi transparent.
Viscosity	30 Poise.
Specific Gravity	1.03±0.02
Solid by Weight %	49±2
Covering Rate (2 coat 15% dilution)	10-12m ² /L
Drying Time	Touch dry :1 hr. Recoatable : 3 hrs.

SURFACE PREPARATION

Surface should be dry, clean & dust free from all loose particles.

APPLICATION DATA

Application Methods	Brush & roll.
Thinning / Cleaning of Tools	Water.

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	12 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(1) - Jan 2014

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.