

TECHNICAL DATA SHEET

(Professional Use Only)

NUMIX PLASTICIZER

PRODUCT DESCRIPTION

Numix Plasticizer is designed to increase Flexibility, impact resistance, chip resistance, And U.V. protection in Numix Top Coat 2K Products, it mixes easily and does not affect Dry or cure times

FEATURES

01. Flexible additive.
02. Highly versatile and compatible to Numix Products.
03. General Purpose Item and compatible with Numix products.

RECOMMENDED USE:

To improve the flexibility of Numix 2K primer Numix top coat 2K, and Numix clear coat 2K and over a wide variety of semi-rigid and flexible plastic parts.



SURFACE PREPARATION:

Surface should be well prepared to obtain excellent smooth surface. At the time of application it should be clean and dry.

Technical Information

Colors	Slightly Yellowish.
Flash Point	27°C
Volatile organic compounds (VOC)	550.0 gm/liter

APPLICATION DATA

	Mixing Ratio	5 - 10% for a liter of paint to be added at spraying viscosity mix well after application.
	Pot Life @ 25° C	3-4 hrs. After mixing

MISCELLANEOUS DATA

STORAGE The product must be stored according to National Regulations. The product should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.

SAFETY / HEALTH Ensure good ventilation during application and drying. Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. Keep out of reach of children.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.