



## NATIONAL GLEAN EMULSION (LVOC)

DESCRIPTION	It is specially formulated exterior water based emulsion based on selected type of latex and extenders mixture which ensures long lasting performance with low volatile organic compounds level complies with EU directive No.2004/42/CE phase II.
RECOMMENDED USE	Exterior cementitious substrates.

### TECHNICAL INFORMATION

Colors	White
Finish	Flat
Specific Gravity	1.37 ± 0.02
Solid by Weight %	58 ± 2
Covering Rate (2 coat 15% maximum dilution)	4 m <sup>2</sup> /L.
Drying Time	Touch Dry : 1 hr. Recoatable : 3 hrs

### SURFACE PREPARATION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application method.

### APPLICATION DATA

Application Methods	Brush / Roller
Thinning / Cleaning of Tools	Water

### RECOMMENDED APPLICATION SYSTEM

Priming	National Bond Top	: 2 Coats
Top coat	National Glean Emulsion (LVOC)	: 2 Coats

### INTERNATIONAL TEST CERTIFICATE

1.	Volatile Organic Content (g/l) BS EN ISO 11890 - 2:2006 Vinci Technology Center (UK)	13.5
----	--	------

### MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	18 months.
SAFETY / HEALTH	- Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE NO. & DATE	( 2 ) - June 2017

**NOTE:** We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.