



NATIONAL EMULSION PURE-CRYL

DESCRIPTION	Based on durable Pure Acrylic, weather and UV resistance , it provides a long-lasting protection to both interiors and exteriors. It has excellent flow, opacity and washability .
RECOMMENDED USE	As an Exterior , on Concrete, Gypsum Boards, Plaster , Cement Sheeting and rendered Block work.

TECHNICAL INFORMATION

Colors	White
Finish	Matt.
Specific Gravity	1.48 ± 0.02
Solid by Weight %	59 ± 2%
PH	8 - 9
VOC (Volatile Organic Compounds)	<30 gm/L
Covering Rate (2 coats 10% dilution)	10 -12 m ² /Lit.

SURFACE PREPARATION

If the surface needs to be prepared before painting, Bond Top Alkali Resistant is suitable.

APPLICATION DATA

Application Methods	Brush, Roller, Airless or Conventional spray.
Thinning / Cleaning of Tools	Water (20 %)
Guiding Data for Airless Spray	Nozzle Tip: 0.021" - 0.027" Nozzle Pressure 2100 P.S.I. Spray Angle: 65° - 80°

CONDITIONS DURING APPLICATION

The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protectors. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE NO. & DATE	

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.