



NATIONAL FINE TEX

DESCRIPTION	A Styrene Acrylic base emulsion containing Quartz aggregates, gives a smooth textured decorative finish which is tough, flexible and weather resistant.
RECOMMENDED USE	For Indoor and Outdoor applications.

TECHNICAL INFORMATION

Colors	As per shade card.
Finish	Matt, Smooth - Textured.
Viscosity	55 - 60 Poise.
Specific Gravity	1.53 ± 0.05
Solid by Weight %	75 ± 1%
Theoretical Spreading Rate	1 - 2 m ² /Lit depending on Pattern & Roll used.
Drying Time	Touch dry : 1 - 2 hrs. Recoatible: 3 - 4 hrs.

SURFACE PREPARATION

Apply **National Bond Sealer** on masonry surfaces and **National Undercoat Primer** for wood.

APPLICATION DATA

Application Methods	Roller, Spray.
Thinning	Ready for use.
Cleaning of Tools	Water
Mixing Ratio	Single pack.

MISCELLANEOUS DATA

STORAGE	The product must be stored according to National Regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	36 months.
SAFETY / HEALTH	<ul style="list-style-type: none"> - Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. While painting it is advisable to wear eye protector. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner. - Keep out of reach of children.
TDS ISSUE No. & DATE	(3) - June 2017

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.